

4

Reporting Aggregated Data Using the Group Functions

Objectives

After completing this lesson, you should be able to do the following:

- **Identify the available group functions**
- **Describe the use of group functions**
- **Group data by using the `GROUP BY` clause**
- **Include or exclude grouped rows by using the `HAVING` clause**

What Are Group Functions?

Group functions operate on sets of rows to give one result per group.

EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600
	7000
10	4400


**Maximum salary in
EMPLOYEES table**

MAX(SALARY)
24000

■■■
20 rows selected.

Types of Group Functions

- **AVG**
- **COUNT**
- **MAX**
- **MIN**
- **STDDEV**
- **SUM**
- **VARIANCE**



Group Functions: Syntax

```
SELECT      [column,] group_function(column), ...
FROM        table
[WHERE      condition]
[GROUP BY  column]
[ORDER BY  column];
```

Using the AVG and SUM Functions

You can use AVG and SUM for numeric data.

```
SELECT AVG(salary), MAX(salary),  
       MIN(salary), SUM(salary)  
FROM   employees  
WHERE  job_id LIKE '%REP%';
```

AVG(SALARY)	MAX(SALARY)	MIN(SALARY)	SUM(SALARY)
8150	11000	6000	32600

Using the MIN and MAX Functions

You can use MIN and MAX for numeric, character, and date data types.

```
SELECT MIN(hire_date), MAX(hire_date)
FROM   employees;
```

MIN(HIRE_	MAX(HIRE_
17-JUN-87	29-JAN-00

Using the COUNT Function

COUNT (*) returns the number of rows in a table:

1

```
SELECT COUNT(*)  
FROM employees  
WHERE department_id = 50;
```

COUNT(*)
5

COUNT (*expr*) returns the number of rows with non-null values for the *expr*:

2

```
SELECT COUNT(commission_pct)  
FROM employees  
WHERE department_id = 80;
```

COUNT(COMMISSION_PCT)
3

Using the DISTINCT Keyword

- `COUNT(DISTINCT expr)` returns the number of distinct non-null values of the *expr*.
- To display the number of distinct department values in the `EMPLOYEES` table:

```
SELECT COUNT(DISTINCT department_id)  
FROM employees;
```

COUNT(DISTINCTDEPARTMENT_ID)
7

Group Functions and Null Values

Group functions ignore null values in the column:

1

```
SELECT AVG(commission_pct)
FROM employees;
```

AVG(COMMISSION_PCT)

.2125

The NVL function forces group functions to include null values:

2

```
SELECT AVG(NVL(commission_pct, 0))
FROM employees;
```

AVG(NVL(COMMISSION_PCT,0))

.0425

Creating Groups of Data

EMPLOYEES

DEPARTMENT_ID	SALARY
10	4400
20	13000
20	6000
50	5800
50	3500
50	3100
50	2500
50	2600
60	9000
60	6000
60	4200
80	10500
80	8600
80	11000
90	24000
90	17000

4400

9500

3500

6400

10033

**Average
salary in
EMPLOYEES
table for each
department**

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

...

20 rows selected.

Creating Groups of Data: GROUP BY Clause Syntax

```
SELECT    column, group_function(column)
FROM      table
[WHERE    condition]
[GROUP BY group_by_expression]
[ORDER BY column];
```

You can divide rows in a table into smaller groups by using the GROUP BY clause.

Using the GROUP BY Clause

All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id ;
```

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

8 rows selected.

Using the GROUP BY Clause

The GROUP BY column does not have to be in the SELECT list.

```
SELECT  AVG(salary)
FROM    employees
GROUP BY department_id ;
```

AVG(SALARY)	
	4400
	9500
	3500
	6400
	10033.3333
	19333.3333
	10150
	7000

Grouping by More Than One Column

EMPLOYEES

DEPARTMENT_ID	JOB_ID	SALARY
90	AD_PRES	24000
90	AD_VP	17000
90	AD_VP	17000
60	IT_PROG	9000
60	IT_PROG	6000
60	IT_PROG	4200
50	ST_MAN	5800
50	ST_CLERK	3500
50	ST_CLERK	3100
50	ST_CLERK	2600
50	ST_CLERK	2500
80	SA_MAN	10500
80	SA_REP	11000
80	SA_REP	8600

...

20	MK_REP	6000
110	AC_MGR	12000
110	AC_ACCOUNT	8300

20 rows selected.

Add the salaries in the EMPLOYEES table for each job, grouped by department

DEPARTMENT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD_PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.

Using the GROUP BY Clause on Multiple Columns

```
SELECT  department_id dept_id, job_id, SUM(salary)
FROM    employees
GROUP BY department_id, job_id ;
```

DEPT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD_PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.

Illegal Queries Using Group Functions

Any column or expression in the `SELECT` list that is not an aggregate function must be in the `GROUP BY` clause:

```
SELECT department_id, COUNT(last_name)
FROM employees;
```

```
SELECT department_id, COUNT(last_name)
      *
ERROR at line 1:
ORA-00937: not a single-group group function
```

Column missing in the `GROUP BY` clause

Illegal Queries Using Group Functions

- You cannot use the **WHERE** clause to restrict groups.
- You use the **HAVING** clause to restrict groups.
- You cannot use group functions in the **WHERE** clause.

```
SELECT  department_id, AVG(salary)
FROM    employees
WHERE   AVG(salary) > 8000
GROUP BY department_id;
```

```
WHERE  AVG(salary) > 8000
      *
ERROR at line 3:
ORA-00934: group function is not allowed here
```

Cannot use the **WHERE clause to restrict groups**

Restricting Group Results

EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600
...	...
20	6000
110	12000
110	8300

20 rows selected.

The maximum salary per department when it is greater than \$10,000

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000

Restricting Group Results with the HAVING Clause

When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are displayed.

```
SELECT      column, group_function
FROM        table
[WHERE      condition]
[GROUP BY  group_by_expression]
[HAVING    group_condition]
[ORDER BY  column];
```

Using the HAVING Clause

```
SELECT  department_id, MAX(salary)
FROM    employees
GROUP BY department_id
HAVING  MAX(salary)>10000 ;
```

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000

Using the HAVING Clause

```
SELECT  job_id, SUM(salary) PAYROLL
FROM    employees
WHERE   job_id NOT LIKE '%REP%'
GROUP BY job_id
HAVING  SUM(salary) > 13000
ORDER BY SUM(salary);
```

JOB_ID	PAYROLL
IT_PROG	19200
AD_PRES	24000
AD_VP	34000

Nesting Group Functions

Display the maximum average salary:

```
SELECT  MAX(AVG(salary))  
FROM    employees  
GROUP BY department_id;
```

MAX(AVG(SALARY))
19333.3333

Summary

In this lesson, you should have learned how to:

- Use the group functions COUNT, MAX, MIN, and AVG
- Write queries that use the GROUP BY clause
- Write queries that use the HAVING clause

```
SELECT    column, group_function
FROM      table
[WHERE    condition]
[GROUP BY group_by_expression]
[HAVING   group_condition]
[ORDER BY column];
```

Practice 4: Overview

This practice covers the following topics:

- **Writing queries that use the group functions**
- **Grouping by rows to achieve more than one result**
- **Restricting groups by using the `HAVING` clause**